

>STAINLESS INDUSTRIAL VALVES

MODEL -RV- SGV



Gate Valve

Class 200lb
Inside Screw Bonnet
Wedge Disc
Integral Seat
Non Rising Stem

Specifications

Pressure Rating 200Psi WOG
Temperature Range -20 to 350F
Ends : BSP

ITEM	DESCRIPTION	MATERIAL
1	Body and Bonnet	CF8M
2	Stem	316
3	Disc	CF8M
4	Gasket	PTFE
5	Stop Ring	316
6	Washer	316
7	Packing	PTFE
8	Gland	304
9	Handwheel & Nut	Alum
10		
11		

ITEM	8mm	10mm	15mm	20mm	25mm	32mm	40mm	50mm	
Length			55mm	66mm	70mm	75mm	85mm	95mm	
Wgt/kg			0.40kg	0.54kg	0.69kg	0.98kg	1.50kg	2.26kg	

MODEL -RV- SGLV



Globe Valve

Class 200lb
Inside Screw Bonnet
Swivel Disc
Integral Seat
Non Rising Stem

Specifications

Pressure Rating 200Psi WOG
Temperature Range -20 to 350F
Ends : BSP

ITEM	DESCRIPTION	MATERIAL
1	Body and Bonnet	CF8M
2	Bonnet	316
3	Stem	316
4	Disc	CF8M
5	Gasket	PTFE
6	Stop Ring	316
7	Washer	316
8	Packing	PTFE
9	Gland	304
10	Handwheel & Nut	Alum
11		

ITEM	8mm	10mm	15mm	20mm	25mm	32mm	40mm	50mm	
Length			68mm	84mm	86mm	102mm	112mm	118mm	
Wgt/kg			0.42kg	0.57kg	0.73kg	1.12kg	1.84kg	199kg	

MODEL -RV- SYS



Y Type Strainer

For Chemical and Industrial applications

Specifications

Pressure Rating 600Psi WOG
Temperature Range 230C
Ends : BSP

ITEM	DESCRIPTION	MATERIAL
1	Body	CF8M
2	Screen	316
3	Gasket	Teflon
4	Bonnet	CF8M
5	O Ring	Teflon
6		
7		
8		
9		
10		
11		

ITEM	8mm	10mm	15mm	20mm	25mm	32mm	40mm	50mm	
Length			60mm	73mm	85mm	100mm	108mm	138mm	
Wgt/kg			0.17kg	0.24kg	0.41kg	0.55kg	0.74kg	1.33kg	
Mesh			1mm	1mm	1mm	1mm	1mm	1mm	